



Automatic Ferrous Cutting Machine



Features:

- Automatic cutting cycle
- Automatic feed rate
- Auto shut-off & unclamping at end of Cut
- Automatic piece counter
- Up to 3 cut-off Indexes for longer pieces
- 230/460/60/3 electricals
- Two speeds for versatility
- Totally enclosed fan-cooled motor
- Enclosed worm gear drive for trouble-free operation
- Cast iron construction
- Self-centering vise hydraulic double vise
- Flood Coolant System
- Heavy Duty Sheet Metal Base
- Tool kit
- Circular saw blade
- Operation and maintenance manual
- Two (2) year limited warranty

Optional Equipment:

- 5 foot roller stock table
- 10 foot roller stock table

Specification

FHC350A

Drive Motor	3/2 hp (2/1.5kw)
Electricals	208/230v. or 460v. - 3ph
Control	110v.
Coolant	Standard
Spindle Speeds (rpm)	70/35
Max. Blade Size	14" (350mm)
Max. Clamping Capacity	4.75" (120mm)
Feed Length Range	
Single stroke	.2" - 27.5" (5-700mm)
Double stroke	.2" - 55" (5-1400mm)
Single stroke	.2" - 82.5" (5-2100mm)
Recommended Cutting Capacity	
Round tube @ 90°	4.33" (110mm)
Square tube @ 90°	4" (100mm)
Rectangular tube @ 90°	4.33" x 2" (110 x 50mm)
Round solid @ 90°	2.36" (60mm)
Square solid @ 90°	2" (50mm)
Dimensions	
Length x Width	86" x 47"
Height	63"
Net Weight	1,984 lbs. (900kg)
Shipping Weight	2,315 lbs. (1050kg)